



2RXXAB

| 项目 Item | 规格 Specification | | | | | | | 单位 Unit |
|---|------------------|------------------|-------------------|-------------------|-------------------|-------------------|-------------------|------------|
| | 2R75AB | 2R90AB | 2R200AB | 2R230AB | 2R350AB | 2R400AB | | |
| 标称直流击穿电压 Nominal DC Spark-over Voltage (100V/S) | 75 $\pm 20\%$ | 90 $\pm 20\%$ | 200 $\pm 20\%$ | 230 $\pm 20\%$ | 350 $\pm 20\%$ | 400 $\pm 20\%$ | 500 $\pm 20\%$ | V |
| 最大冲击击穿电压 Maximum impulse spark- over voltage (1KV/us) | 550 | 550 | 600 | 650 | 900 | 950 | 1000 | V |
| 耐冲击电流 (短波) Impulse discharge current (8/20us, 10 times) (a+b)-e | 0.5/1 | 0.5/1 | 0.5/1 | 0.5/1 | 0.5/1 | 0.5/1 | 1 | KA |
| 耐冲击电压 Impulse withstanding voltage (10/700us) | 4 | 4 | 4 | 4 | 4 | 4 | 4 | KV |
| 最小绝缘电阻 Minimum insulation resistance | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | M Ω |
| 最大极间电容 Maximum capacitance (1MHZ) | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | pF |